

Link do produktu: <https://www.multiproject.com.pl/miernik-cyfrowy-uniw-uni-t-ut-171c-loz-oled-p-23922.html>



Miernik cyfrowy uniw. Uni-T UT-171C LoZ OLED

Cena brutto	1 692,48 zł
Cena netto	1 376,00 zł
Czas wysyłki	24 godziny
Numer katalogowy	26427
Producent	Brak

Opis produktu

Seria UT171 to multimetry klasy przemysłowej używane przez profesjonalistów. Wbudowane wyjście fali prostokątnej jest przydatne do rozwiązywania problemów z sygnałami sterowania przemysłowego. Jego funkcja LoZ (ACV) może być wykorzystana do identyfikacji napięcia szczytkowego (duchowego) w dużych kondensatorach. Wyświetlacz OLED UT171C jest idealny do pracy w niskich temperaturach do -30°C .

1. Pomiar AC+DC
2. Szczyt przytrzymaj
3. Akumulator
4. Filtrowanie dolnoprzepustowe VFC
5. Komunikacja USB/Bluetooth

Specifications	Range	UT171C
DC voltage (V)	1000V	$\pm(0.025\%+5)$
AC voltage (V)	1000V	$\pm(0.4\%+40)$
DC current (A)	10A	$\pm(0.15\%+2)$
AC current (A)	10A	$\pm(0.75\%+5)$

Resistance (Ω)	60M Ω	$\pm 0.05\%$ □ 2)
Admittance (S)	60nS	$\pm 1\%$ □ 10)
Capacitance (F)	60mF	$\pm 2.5\% \pm 40$
Frequency (Hz)	10Hz-10MHz	$\pm 0.01\% \pm 5$
Temperature (°C)	-40°C-1000°C	$\pm 1\% \pm 30$
Temperature (°F)	-40°F-1832°F	$\pm 1.5\% \pm 50$
Features		
Display count		60000
Auto-Manual range		tak
Bandwidth (Hz)	100kHz	tak
4-20mA loop	0-100%	tak
LoZ (ACV)	Around 3k Ω	tak
Diode	Around 3V	tak
Continuity buzzer		tak
Duty cycle	0.1%-99.9%	tak
NCV Data hold MAX/MIN		tak
Relative mode		tak

Data storage		9999
Display type		OLED
Analog bar graph		31
LCD backlight		tak
Mis-plug alarm		tak
Low battery indication		tak
Auto power off		tak
Input protection		tak
Input impedance for DCV		tak
Input impedance for DCV	Around 1G Ω	tak
General Characteristics		
Power	7.4V 2000mAh Li-ion battery	
Display	70.6mm x 35.3mm	
Product color	Red and grey	
Product net weight	384g	
Product size	206mm x 95mm x 55mm	

Standard accessories	Batteries, test leads, point contact temperature probe, USB interface cable, power adaptor, PC software CD
Standard individual packing	Gift box, carrying bag, English manual
Standard quantity per carton	5pcs
Standard carton measurement	390mm x 310mm x 205mm (0.55CBM per standard carton)
Standard carton gross weight	5.6kg
Optional accessory	Bluetooth adaptor (UT-D07)