

Link do produktu: <https://www.multiproject.com.pl/rejestrator-4w1-4-kanalowy-xvr301-04q-p-23395.html>

Rejestrator 4w1 4-kanałowy XVR301-04Q



Cena brutto	587,94 zł
Cena netto	478,00 zł
Czas wysyłki	24 godziny
Numer katalogowy	25788
Producent	Brak

Opis produktu

- Obsługa formatów wideo H.265/H.264
- Obsługa dźwięku przez kabel koncentryczny
- Obsługa kamer TVI, AHD, CVI, CVBS, IP z dostępem adaptacyjnym
- 4-kanałowe wejście BNC
- Obsługa 1-kanałowego wyjścia HDMI, 1-kanałowego wyjścia VGA do 1920*1080
- Duża odległość transmisji przez kabel koncentryczny

Model	NVR301-04Q	NVR301-08Q
Video/Audio Input		
Analog Video Input	4-ch, BNC	8-ch, BNC
IP Video Input	2-ch(only IP up to 6ch),each channel up to 4K	4-ch(only IP up to 12ch),each channel up to 4K
Supported Analog Camera Types	Support AHD input: 8MP@15fps (channel1) 5MP@20fps 4MP@30fps 3MP@30fps (channel1) 1080P@30fps 720P@60fps Support TVI input: 8MP@15fps(channel1) 5MP@20fps 4MP@30fps 3MP@30fps (channel1) 1080P@30fps 720P@60fps Support CVI input: 8MP@15fps(channel1) 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps Support CVBS input	Support AHD input: 8MP@15fps(channel1-channel2) 5MP@20fps 4MP@30fps 3MP@30fps (channel1 -channel2) 1080P@30fps 720P@60fps Support TVI input: 8MP@15fps(channel1-channel2) 5MP@20fps 4MP@30fps 3MP@30fps (channel1 - channel2) 1080P@30fps 720P@60fps Support CVI input: 8MP@15fps(channel1-channel2) 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps Support CVBS input
Audio Input	1-ch, RCA	1-ch, RCA



Two-way Audio	1-ch, RCA	1-ch, RCA
Channel Associated Audio	1-ch,RCA	1-ch,RCA
Network		
Incoming Bandwidth	48Mbps	56Mbps
Outgoing Bandwidth	60Mbps	64Mbps
Remote Users	128	
Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE	
Video/Audio Output		
CVBS Output	1-ch, BNC	1-ch, BNC
VGA Output	1920x1080p@60Hz, 1920x1080p@50Hz, 1600x1200@60Hz, 1280x1024@60Hz, 1280x720@60Hz, 1024x768@60Hz	
HDMI Output	1920x1080p@60Hz, 1920x1080p@50Hz, 1600x1200@60Hz, 1280x1024@60Hz, 1280x720@60Hz, 1024x768@60Hz	1920x1080p@60Hz, 1920x1080p@50Hz, 1600x1200@60Hz, 1280x1024@60Hz, 1280x720@60Hz, 1024x768@60Hz
Audio Output	1-ch, RCA	
Synchronous Playback	4-ch	8-ch
Encoding		
Recording Resolution	8MP Line/5MP Line/4MP Line /3MP/1080P/960P/720P/960H/D1/4CIF/CIF	8MP Line/5MP Line/4MP Line /3MP/1080P/960P/720P/960H/D1/4CIF/CIF
Recording Frame Rate	Main stream: 8MP Line@8fps/channel1 SMP Line@ 12fps 4MP Line@ 15fps 3MP@ 15fps/channel1 1080P@ 15fps 720P@ 30fps Sub stream: D1 @ 30fps(Max)	Main stream: 8MP Line@8fps channel1-channel2 SMP Line@ 12fps 4MP Line@ 15fps 3MP@ 15fps/channel1 - channel2 1080P@ 15fps 720P@ 30fps Sub stream: D1 @ 30fps(Max)

Hard Disk	
SATA	1 SATA interfaces
Capacity	Up to 6TB for each HDD
External Interface	
Network Interface	1RJ45 10M/100M self-adaptive Ethernet Interface
USB Interface	Rear panel □ 2 x USB2.0
Serial Interface	1 x RS485
General	
Power Supply	12V DC Power Consumption: 7.8 W (without HDD)
Working Environment	-10°C ~ +55°C (+14°F ~ +131°F), Humidity 790% RH(non-condensing)
Dimensions(W-D-H)	260mm x 240mm x 46mm (10.2" x 9.4" x 1.8")
Weight (without HDD)	1.1 Kg (2.43lb)